

KNIPEX StepCut

Additionally hardened, precision-ground blades: lighter, cleaner cut without crushing



KNIPEX StepCut – Cable Shears

Cable cutting made easy: innovative step cutting separates wires one by one to save energy

- ➤ Small, light, strong: comfortable cutting without crushing and just 160 mm in size
- ▶ Noticeably less effort: the gradations cut wires one after the other; cutting is up to 40 % easier than with standard cable shears of the same length!
- ► Ergonomic handle design: optimal cutting feel even for larger cable diameters
- > Cuts multi-core stranded copper and aluminium cables up to Ø 15 mm (50 mm²)
- > Cuts solid copper and aluminium cables up to 5 x 4 mm²
- > Cuts without crushing
- > Bolted joint: precise, effortless, durable
- > Pinch guard fitted for safe work
- > Not suitable for steel wire and hard drawn copper conductors
- > Cutting edges additionally induction-hardened, cutting edge hardness at least 56 HRC
- > High-grade special tool steel, forged, oil-hardened






95 11 160



95 12 160







Cuts solid Cu- and Al-cable up to 5 x 4 mm²



Bolted joint: precise, smooth-running, durable; with pinch guard

| | | EAN | ←→ | | | | Cutting o | capacities | | |
|--------------|---|----------|-----------|-------------------|---------------|--|-----------|-----------------|-------|-----|
| | | | | | | | ♦ | ⊕ | | 7.7 |
| Article No. | | 4003773- | mm | | Tool | Handles | Ø mm | mm ² | AWG | g |
| 95 11 160 | N | 085904 | 160 | | burnished | plastic coated | 15.0 | 50 | 1/0 | 180 |
| 95 11 160 SB | N | 085911 | 160 | | burnished | plastic coated | 15.0 | 50 | 1 / 0 | 205 |
| 95 12 160 | N | 085928 | 160 | | burnished | with multi-component grips | 15.0 | 50 | 1/0 | 220 |
| 95 12 160 SB | N | 085935 | 160 | | burnished | with multi-component grips | 15.0 | 50 | 1/0 | 245 |
| 95 16 160 | N | 085966 | 160 | <u>A</u> 1000 V △ | chrome plated | insulated with multi-component grips, VDE-tested | 15.0 | 50 | 1/0 | 225 |
| 95 16 160 SB | N | 085898 | 160 | ☆ 1000 V △ | chrome plated | insulated with multi-component grips, VDE-tested | 15.0 | 50 | 1/0 | 250 |